



### EC Type-Approval Certificate

for non-original motorcycle exhaust



Approval No.:	e26*97/24*2013/60/9/111*8032*00				
Issued by:	SLOVENIAN TRAFIC SAFETY AGENCY Vehicle department Kotnikova ulica 19a, SI-1000 LJUBLJANA, SLOVENIA				
Place & date of type-approval:	LJUBLJANA, 12.06.2015				
Report No.:	15-00077-CM-GBM-00				
Issued by:	TÜV SÜD Auto Service GmbH Westendstrasse 199 DE-80686 MÜNCHEN				
Date of issue:	08.06.2015				
Approval identification:	e26 8032 (9)				

Technical data of exhaust system

Type and version of exhaust: M-HCQOO4, M-HCQOO4/L, M-HCQOO4/R.

Marking: Engraved by laser / plate fixed with rivets

## Field of application:

Manufacturer	Commercial description	Vehicle type ( and no. of homologation ) **	Engine type	Component parts, dimensions in mm	Dimensions of the part in mm or original part / replacement part	Akrapovic part no. Or homologation no.
Motor Comp. / Harley TEURC 1 Davidson FAHT EI FAHT SI FLETTO FAHT	FLHR Raad King FLHRE Road King Classic FLHT Electra Bilde Standard FLHTEU Ultra Classic Electra Bilde FLHX Street Bilde FLHX Street Bilde FLHP Road King Police FLHTP Electra Bilde Police FLHTP Electra Bilde Classic FLTRX Road Bilde Custom FLHTK Electra Bilde FLHR Road King FLHRE Road King FLHRE Road King FLHRE Lectra Bilde Elassic FLHTE Electra Bilde Elassic FLHTE Electra Bilde Elassic FLHTE Electra Bilde Elassic FLHTE Electra Bilde Elassic	FL2 (e4*1918*00) FL2 (e4*1918*01)	#4# #4# #4# #4# ### #M# #4# #4# ### #M# ### ##	Header pipes with Catalityc converter Link pipe right with Exup valve Link pipe left with Exup valve Sound Kit Electronic control unit Silencer right (Outlet pipe a 28) Silencer left (Outlet pipe a 78)	Original parts  Hexagonal 117 x 111 mm Total length 503.9  Hexagonal 117 x 111 mm Total length 503.9	LP-H0T03* LP-HDT03* P-HR84-M EI IR-057586 M-HC0004 e28*8032*(9), E26 92R-018032 M-HC0004 e26*8032*(9), E26 92R-018032
	Electra Bilde FLHTX Electra Bilde FLHTX Electra Bilde FLHTX Street Bilde FLHP Road King Police FLHTP Electra Bilde Police FLTTY Road Bilde Ultra FLTRX Road Bilde Custom	FL2 (e4*1918*04)	#4# / #M# #M# #4# / #M# #M# #M# #M# #M#			
	FLHR ANV Road King 110 Anv. Edit. FLHTX ANV Electra Glide Ultra Limited 110 Anv. Edit. FLHRC Road King Classic FLHTCU TC Electra Glide	FL2 (e4*1918*07)	_#M# _#M#			
	Ultra Classic FLHTK Ultra Limited FLHX Street Blide FLHIP Police Electra Blide FLHIP Police Road King FLHRX Road Blide Special	FL3 (e4*2924*00)	#4# #4# #2# #2# #2# #2#			
	FLIXAS Koad bilde special FLHXS Street Glide Special FLHTKL Ultra Limited Low FLHTCUL TC E-Glide Ultra Classic Low	FL3 (e4*2924*02)	#2# #4# #4#	-		

<sup>\*\*</sup> All extensions from no. (e4\*1918\*00) till no. (e4\*1918\*07) are included in this approval certificate.

<sup>\*\*</sup> All extensions from no. (e4\*2924\*00) till no. (e4\*2924\*02) are included in this approval certificate.

# To be filled out by Akrapovič representative: Date of purchase: Stamp & signature: Muffler repack kit service intervals The durability of the damping material depends on the type of motorcycle, riding style, mileage etc. Normally, single and twin cylinder engines produce a stronger exhaust gas wave pulse and a higher temperature. Often, riding on a race track requires noise control. The insulating

material should be replaced when you notice any visual changes on the muffler sleeve material or when the muffler exceeds the noise limit.

Performed by:\_\_\_\_\_\_ Performed by:\_\_\_\_\_

Stamp & signature: Stamp & signature:

Date: Date:

Performed by: Performed by:

Stamp & signature: Stamp & signature:

Date:

# Maintenance

1. Clean the titanium muffler outer sleeves with a multi-purpose spray lubricant (WD-40 or equivalent) and carbon-fiber outer sleeves with soft and dry cloth. Do not use aggressive chemical cleaners, because they can damage the sticker. A change in the color of the exhaust system is normal due to the high temperatures.

Please check the muffler visually before every season.

- 2. The wearing out of the muffler silencing material depends on the type of the motor and riding style. Contact your dealer/serviceman if visible changes appear on muffler's outer sleeve or the noise level is increased.
- 3. Periodically make sure all the bolts are sufficiently tight.

# **Exclusion of Certain Liability**

- 1. The manufacturer, importer or dealer shall not be liable for any incidental damage including personal injury or any other damages caused by improper installation or operation of the Akrapovič exhaust system. When installing the Akrapovič exhaust system be careful that the exhaust system does not touch other parts sensitive to high temperature.
- 2. Akrapovič makes no representation or warranties with regard to damage caused by the improper installation, use and maintenance of the Akrapovič exhaust system. The warranty is limited to defects recognized by our technical department and to normal use, and excludes items subject to normal wear (gaskets and damping wool). The guarantee is void in case of accident, modification, improper or competition use.
- 3. Do not attempt to install the Akrapovič exhaust system on a motorcycle for which it was not made or tested by Akrapovič.
- 4. When the exhaust system gets very hot during operation, be careful not to burn yourself on the exhaust system or parts which are in direct contact with it, even when the motor is not running. Also protect other people, especially children, from the injuries mentioned above.
- 5. In some cases Akrapovič exhaust system kits contain chemical products (ceramic antiseizing grease). Handle with care, do not inhale or swallow. Avoid excessive contact with skin, eyes or mucous membranes. Keep out of the reach of children.
- **6.** Technical specifications of Akrapovič exhaust systems and related products subject to change without notice.