

e24 0142 (9)



EC Type-Approval Certificate

for non-original motorcycle exhaust system



502818

Approval No.:	e24*97/24*2009/108/9/III*0142*03
Issued by:	NATIONAL STANDARDS AUTHORITY OF IRELAND Certification Services - Operations Manufacturing 1 swift Square, Northwood, Santry, Dublin 9, Ireland
Place & date of type-approval:	Dublin, 07.12.2013
Report No.:	10-00103-CM-GBM-03
Issued by:	TÜV SÜD AUTOMOTIVE GMBH TÜV SÜD Gruppe DE-80686 MÜNCHEN
Date of issue:	28.11.2013
Approval identification:	e24 0142 (9)

Type and version of exhaust: M-HR026 / M-HR02601T, M-HR02601SS, M-HR02602T, M-HR02602SS, M-HR02603T, M-HR02603SS, M-HR02604T, M-HR02604SS, M-HR02605T, M-HR02605SS.

Marking: Engraved by laser / plate fixed with rivets.

Field of application:

Manufacturer / Trade Mark	Commercial description	Vehicle type (and no. of homologation)	Engine type	Component parts, dimensions in mm	Dimensions of the part in mm or original part / replacement part	Akrapovic part no. Or homologation no.
YAMAHA Motor Espana S.A. / YAMAHA	X-MAX 250 / YP 250 R	SB16 (e9*0039*)	G344E / G362E	Header pipes	Original part	-
	X-MAX 250 / YP 250 R	SB22 (e9*0362*)	G389E / G3A7E	Link pipe		L-xxx
	X-MAX 125 / YP 125 R	SE32 (e9*0052*)	E384E	Catalytic converter	ø 62 x 65	P-KAT-028, e24*0150*(5)
	X-MAX 125 / YP 125 R	SE54 (e9*0395*)	E362E	Silencer	Hexagonal 110 x 140	M-HR026, e24*0142*(9)
M.B.K. Industrie (F) / YAMAHA	X-MAX 250 / YP 250 R	SB25 (e13*0494*)	G389E / G3A7E	Outlet pipes ø 28	Length without end caps 350	
	X-MAX 250 / YP 250 R	SB26 (e13*0680*)	G383E			
	X-MAX 125 / YP 125 R	SE64 (e13*0501*)	E362E			
	X-MAX 125 / YP 125 R	SE68 (e13*0654*)	E3M1E			
	X-City 125	SE43 (e13*0203*)	E3A5E			
YAMAHA Motor Espana S.A. / MBK	X-City 250 / YP 250	SB19 (e13*0190*)	G358E			
	Scyrcruiser 125	SE32 (e9*0052*)	E384E			
	Scyrcruiser 125	SE54 (e9*0395*)	E362E			
	Scyrcruiser 250	SB22 (e9*0362*)	G389E / G3A7E			
M.B.K. Industrie (F) / MBK	Scyrcruiser 125	SE64 (e13*0501*)	E362E			
	Scyrcruiser 125	SE68 (e13*0654*)	E3M1E			
	Scyrcruiser 250	SB25 (e13*0494*)	G389E / G3A7E			
	Scyrcruiser 250	SB26 (e13*0680*)	G383E			
	Cityliner 125	SE43 (e13*0203*)	E3A5E			

To be filled out by Akrapovič representative:

Date of purchase: Issued by:

Stamp & signature:

Muffler repack kit service intervals

The durability of the damping material depends on the type of motorcycle, riding style, mileage etc. Normally, single and twin cylinder engines produce a stronger exhaust gas wave pulse and a higher temperature. Often, riding on a race track requires noise control. The insulating material should be replaced when you notice any visual changes on the muffler sleeve material or when the muffler exceeds the noise limit. Please check the muffler visually before every season.

Date: _____

Performed by: _____

Stamp & signature: _____

Date: _____

Performed by: _____

Stamp & signature: _____

Date: _____

Performed by: _____

Stamp & signature: _____

Date: _____

Performed by: _____

Stamp & signature: _____

Date: _____

Performed by: _____

Stamp & signature: _____

Date: _____

Performed by: _____

Stamp & signature: _____

Maintenance

1. Clean the titanium muffler outer sleeves with a multi-purpose spray lubricant (WD-40 or equivalent) and carbon-fiber outer sleeves with soft and dry cloth. Do not use aggressive chemical cleaners, because they can damage the sticker. A change in the color of the exhaust system is normal due to the high temperatures.

2. The wearing out of the muffler silencing material depends on the type of the motor and riding style. Contact your dealer/serviceman if visible changes appear on muffler's outer sleeve or the noise level is increased.

3. Periodically make sure all the bolts are sufficiently tight.

Exclusion of Certain Liability

1. The manufacturer, importer or dealer shall not be liable for any incidental damage including personal injury or any other damages caused by improper installation or operation of the Akrapovič exhaust system. When installing the Akrapovič exhaust system be careful that the exhaust system does not touch other parts sensitive to high temperature.

2. Akrapovič makes no representation or warranties with regard to damage caused by the improper installation, use and maintenance of the Akrapovič exhaust system. The warranty is limited to defects recognized by our technical department and to normal use, and excludes items subject to normal wear (gaskets and damping wool). The guarantee is void in case of accident, modification, improper or competition use.

3. Do not attempt to install the Akrapovič exhaust system on a motorcycle for which it was not made or tested by Akrapovič.

4. When the exhaust system gets very hot during operation, be careful not to burn yourself on the exhaust system or parts which are in direct contact with it, even when the motor is not running. Also protect other people, especially children, from the injuries mentioned above.

5. In some cases Akrapovič exhaust system kits contain chemical products (ceramic anti-seizing grease). Handle with care, do not inhale or swallow. Avoid excessive contact with skin, eyes or mucous membranes. Keep out of the reach of children.

6. Technical specifications of Akrapovič exhaust systems and related products subject to change without notice.